



Français 1 of 1

&DOC=04/082969&TYPE=A2" TARGET="pages">Images

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(11) WO 2004/082969

(13) A2

(21) PCT/DE2004/000541

(22) 17 March 2004 (17.03.2004)

(25) German

(26) German

(30) 103 11 862.4

17 March 2003

DE

(17.03.2003)

(30) 203 20 370.4

10 June 2003

DE

(10.06.2003)

(43) 30 September 2004 (30.09.2004)

(51)⁷ B60H

(54) AIR-CONDITIONING DEVICE FOR THE PASSENGER AREA OF A VEHICLE

(71) W.E.T. AUTOMOTIVE SYSTEMS AG [DE/--]; Rudolf-Diesel-Strasse 12, 85235 Odelzhausen (DE).

(72)

(75) STÖWE, Stefan [DE/DE]; Schillerstrasse 6, 86415 Mering (DE).

(81) AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW


(84) ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG, BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

For information on time limits for entry into the national phase please click [here](#)

Published


-- without international search report and to be republished upon receipt of that report

(57) The invention relates to a device (3) for air-conditioning a vehicle seat (20) comprising an upholstery core (22) in order to provide



support to a passenger, an upper air-distribution device (25) arranged on the front side (27) of the upholstery core (22) opposite the passenger in order to distribute air along the front side (27) of the upholstery core (22), and a lower air distribution device (32) which is arranged on the rear side (30) orientated away from the passenger in order to distribute air along the rear side (27) of the upholstery core (22). Said vehicle seat also comprises a connection device (35) which conducts air between the first and the second air distribution device (25, 32). According to the invention, each of the three devices (25, 32, 35) is provided with an elongate cavity (37) and at least one of said cavities (37) is provided with at least one support element (14), in the form of a wound spring, in the air-guiding cross-section.



Français 
1 of 1